



Universal Programmable Controller TCI2-MOD

The TCI2 is a programmable universal controller with Modbus fieldbus connection. Each control loop may use 2 PI sequences and 2 binary stages. The TCI2 comes with a built-in RS485 communication interface that allows peer-to-peer communication with an operation terminal such as OPA2-(2TH)-VC. Complete parameter sets may be copied by use of an accessory called AEC-PM2 or exchanged with a PC using an RS485-USB converter and the Easyset program. The TCI2 uses the universal X2 operating system.

Applications

- Refrigeration / air conditioning units
- Ventilators
- Humidifying / dehumidifying
- Pressure / pump systems
- and many more...

Functions

- Modbus Communication via RS485 RTU or ASCII
- Two universally configurable control loops:
 - Functions for dehumidifying, set point shift and cascade control
 - Multiple auxiliary functions: heat-cool auto changeover, automatic enable, set point compensation
 - Free heating and cooling with economizer function based on enthalpy or temperature
 - Differential, averaging, min and max functions, enthalpy and dew point calculations
 - Transmitter function for inputs and set points
- 4 selectable universal inputs (VDC, mA, NTC, Pt1000) and 2 analog outputs (VDC, mA)
- 2 relays with each a normally open contact
- 8 freely assigned alarm conditions, selectable state of outputs on alarm condition
- Power Cap protected real-time clock with 48hr power backup
- 7-day programmable schedules, with options including change of set points and direct position of manual outputs
- Password protected programmable user and control parameters

Ordering

| Model | Item | Loop | UI | DO | AO | Functions |
|-------------------------|-----------|------|----|----|----|---|
| TCI2-204.202UC-MOD | 40-110107 | 2 | 4 | 2 | 2 | Controller with Modbus RTU or ASCII communication |
| TCI2-204.202UC-OP-MOD | 40-110109 | 2 | 4 | 2 | 2 | Controller with display and Modbus RTU or ASCII communication |
| TCI2-204.202UC-OP-MOD-L | 40-110110 | 2 | 4 | 2 | 2 | Controller with display, Modbus RTU or ASCII and line voltage |
| AEC-PM2 | 40-500130 | | | | | Plug-In memory module |
| AEX2-MOD | 40-500105 | | | | | Modbus RTU or ASCII communication |
| AEX2-BAC | 40-500106 | | | | | BACnet® MS/TP communication |
| AMM-1 | 40-510022 | | | | | Accessory for cabinet door mounting |

A large range of remote operation terminals may be found on our website. All -VC operation terminals work with this controller.


Technical specifications

Important notice and safety advice


This device is for use as an operating controller. It is not a safety device. Where a device failure could endanger human life and property, it is the responsibility of the client, installer and system designer to add additional safety devices to prevent such a device failure. Ignoring specifications and local regulations may cause equipment damage and endangers life and property. Tampering with the device and misapplication will void warranty.

| | | | |
|--------------------------------------|---|-----------------|--|
| Power supply | Power requirements | TCI2-204.202U | 24 VAC $\pm 10\%$, 50/60 Hz, 15..34 VDC, SELV to HD 384, Class II, 48 VA max |
| | | TCI2-204.202U-L | 85..264 VAC, 50/60 Hz, 120..370 VDC |
| | Power consumption | | Max. 5 VA |
| | Electrical connection | | Removable terminal connectors, wire 0.34...2.5 mm ² (AWG 24...12) |
| | Clock backup | | Min. 48 hours |
| Signal inputs | Universal input | | Input jumper set for voltage or current |
| | Input signal | | 0...10 V or 0...20 mA |
| | Resolution | | 9.76 mV or 0.019 mA (10 bit) |
| | Impedance | | Voltage: 74.8k Ω Current: 158 Ω |
| | Passive input | | Input jumper set to temperature (RT) or digital input (DI) |
| | Type & range: | | NTC (Sxx-Tn10) 10k Ω @25°C: -40...100 °C (-40...212 °F) PT1000 (Sxx-Tp2): -50...205 °C (-58...401 °F) NI1000 (Sxx-Tk5): -50...180 °C (-58...356 °F) |
| Signal outputs | Analog outputs: | Output signal | DC 0...10 V or 0...20 mA |
| | | Resolution | 9.76 mV or 0.019 mA (10 bit) |
| | | Maximum load | Voltage: $\geq 1k\Omega$ Current: $\leq 250\Omega$ |
| | Relay outputs: | AC Voltage | 0...250 VAC, full-load current 3A, locked-rotor 18A. |
| | | DC Voltage | 0...30 VDC, full-load current 3A, locked-rotor 18A. |
| | Insulation strength between relays contacts and system electronics: | | 4000V AC to EN 60 730-1 |
| | between neighbouring contacts: | | 1250V AC to EN 60 730-1 |
| Network | Hardware interface | | RS485 in accordance with EIA/TIA 485 |
| | Max nodes per network | | 128 |
| | Max nodes per segment | | 64 (Vector devices only) |
| | Conductors | | Shielded Twisted Pair (STP) cable |
| | Impedance | | 100 - 130 ohm |
| | Nominal capacitance | | 100 pF/m 16 pF/ft. or lower |
| | Galvanic isolation | | The communication circuitry is isolated |
| | Line termination | | A line termination resistance (120 ohm) shall be connected between the terminals (+) and (-) of the furthestmost node of the network |
| | Network topology | | Daisy chain according EIA/TIA 485 specifications |
| | Recommended maximum length per chain | | 1200 m (4000 ft.) |
| Modbus | Communication standard | | Modbus (www.modbus.org) |
| | Default setting | | 19200 baud rate, RTU 8 data bits, 1 even parity bit, 1 stop bit |
| | Communication speed | | 4800, 9600, 19200, 38400 |
| | Protocol: Data bits | | RTU - 8 data bits, ASCII - 7 data bits, |
| | Parity - stop bit | | no parity - 2 stops, even or odd parity - 1 stop |
| Connection to remote terminal | Hardware interface | | RS485 in accordance with EIA/TIA 485 |
| | Cabling | | Twisted pair cable category 5 or 6 |
| Environment | Operation | | To IEC 721-3-3 |
| | Climatic conditions | | class 3K5 |
| | Temperature | | 0...50 °C (32...122 °F) |
| | Humidity | | <85 % RH non-condensing |
| | Transport & storage | | To IEC 721-3-2 and IEC 721-3-1 |
| | Climatic conditions | | class 3K3 and class 1K3 |
| | Temperature | | -25...70 °C (-13...158 °F) |
| | Humidity | | <95 % RH non-condensing |
| | Mechanical conditions | | class 2M2 |

Technical specifications continued

| | | | |
|------------------|---|--|---|
| Standards |  | conformity EMC directive Low voltage directive | 2014/30/EU 2014/35/EU |
| | Product standards | | |
| General | Automatic electrical controls for household and similar use | | EN 60 730 -1 |
| | Special requirement on temperature dependent controls | | EN 60 730 - 2 - 9 |
| | Electromagnetic compatibility for industrial and domestic sector | | Emissions: EN 60 730-1 Immunity: EN 60 730-1 |
| | Degree of protection | | IP00 to EN 60 529 |
| | Pollution class | | II (EN 60 730-1) |
| | Safety class: TCI2-202.202U | | III (IEC 60536) if SELV is connected to DO, else II |
| | TCI2-204.202U-L | | II (IEC 60536) |
| | Overvoltage category | | III (EN 60 730-1) |
| | Material | | Fire proof ABS plastic (UL94 class V-0) |
| | Dimensions (H x W x D) | | 57 x 93 x 115 mm (2.2 x 3.7 x 4.5) inch |
| | Weight (including package) | | |
| | TCI2 (24V) without display / with display | | 245g (8.6oz) / 290g (10.2oz) |
| | TCI2 (230V) without display / with display | | 275g (9.7oz) / 320g (11.3oz) |

Dimensions, mm (inch)



Selection of actuators and sensors

Temperature sensors

Use Vector Controls NTC sensors to achieve maximum accuracy: SDB-Tn10-20 (duct), SRA-Tn10 (room), SDB-Tn10-20 + AMI-S10 as immersion sensor.

Actuators


Choose modulating actuators with an input signal type of 0-10 V DC or 4-20 mA (Min. and max. signal limitations may be set with parameters).

3-point actuators with constant running time are recommended.


Binary auxiliary devices (e.g. pumps, fans, on/off valves, humidifiers, etc.)

Do not directly connect devices that exceed specified limits in technical specifications – observe startup current on inductive loads.

Connection diagram



85..264 VAC



Configuration Jumpers

The inputs and outputs are configured with wire jumpers. These are located on the bottom of the controller.

AO: Selection of analog output type

Left position:
voltage output (0... 10 V)
factory default

Right position:
current output (0... 20 mA)

| AO1 | |
|-----|----------|
| ■ | 0...10V |
| | 0...20mA |

UI: Selection of universal input type

Left position:
voltage output (0... 10 V)
factory default

Middle position: current input (0... 20 mA)

Right position: RT or dry contact

| UI1 | |
|-----|----------|
| ■ | 0...10V |
| | 0...20mA |
| | RT / DI |

LED-indicators

A status LED is located on the upper left side of the controller housing. During normal operation the LED blinks briefly once every 5 seconds. If there is an alarm or fault condition it will blink every second. On devices with OP the LED display is omitted.

The Modbus slave features a green LED and a red LED for indication of traffic on the RS-485 bus. The green LED is lit when an incoming packet is received, and the red LED is lit when an outgoing packet is transmitted to the bus. At power-up, both LED blink twice simultaneously as a sign of the boot process being completed. A constantly lit LED serves as an indication of a fault condition in the reception or sending process.

Installation

See installation sheet no:

- TCI2 70-000688 (www.vectorcontrols.com)

Wire type

An EIA-485 network shall use shielded, twisted-pair cable for data signalling with characteristic impedance between 100 and 130 ohms. Distributed capacitance between conductors shall be less than 100 pF per meter (30 pF per foot). Distributed capacitance between conductors and shield shall be less than 200 pF per meter (60 pF per foot). Foil or braided shields are acceptable.

Maximum length

The maximum recommended length per segment is 1200 meters (4000 feet) with AWG 18 (0.82 mm² conductor area) cable.

X2 Functional Scope

The controller has the following X2 functions and elements:

| Group | Modules | QTY | Description |
|-------|--------------|-----|--|
| UP | | | User and display parameters |
| UI | 01U to 04U | 4 | Universal inputs, selectable with jumper: RT/DI, mA, VDC |
| | 05U to 08U | 4 | Virtual inputs for operation terminals, bus modules or special functions |
| AL | 1AL to 8AL | 8 | Alarm conditions |
| LP | 1L to 2L | 2 | Control loops |
| Ao | 1A to 2A | 2 | Analog outputs, selectable with jumper: mA, VDC |
| FAN | 1F | 1 | Fan or lead lag modules, 1 to 3 fan speeds, up to 3 switching lead-lag stages each |
| do | 1d to 2d | 2 | Binary outputs with a normally open (NO) relays contact |
| FU | 1FU | 1 | Remote Enable: Activation of the controller based on signal and alarm conditions |
| | 2FU | 1 | Change Operation Mode: Switching occupied and unoccupied with control signals |
| | 3FU | 1 | Heat/Cool Change: Switching heating and cooling based on a control signal |
| | 4FU | 1 | Setpoint Compensation: Summer/winter compensation of setpoint |
| | 5FU | 1 | Economizer (free heating or cooling due to the condition of outside and room air) |
| Co | | | Communication (if a communication module is available) |
| COPY | | | Copying complete parameter sets between run, default and external memory with up to 4 memory locations (AEC-PM2) |
| RTC | | 1 | Real time clock module with 48-hour power back up (keeps clock running during power failure) |
| PRO | Pr01 to Pr12 | 12 | Time schedule programs for 7 days or annual switching events |

Operation manual and configuration

This controller uses the latest generation X2 operating system. Detailed operating instructions for all devices equipped with this operating system can be downloaded here

<http://www.vectorcontrols.com/products/x2>

Also available are programming instructions for technicians and an application database.

The device can be fully configured using EasySet.

EasySet may be downloaded free of charge from www.vectorcontrols.com.

**Efficient use of energy -
for a better future**

Quality - Innovation - Partnership
Vector Controls GmbH

Poststrasse 20, CH-8620 Wetzikon, Schweiz
Tel: +41 41 740 60 50 Fax: +41 41 740 60 51
info@vectorcontrols.com
www.vectorcontrols.com

